



4K UHD



Compatible with Apple Airplay





#### UM670H Series

Design	Stand Type	65": 1 pole (Fixed) 55" / 50" / 43": 1 pole (Swivel)
Diaplay	Sizes	65" / 55" / 50" / 43"
Display	Resolution	3,840 x 2,160 (4K UHD)
Broadcasting	Digital	ATSC, Clear QAM
System	Analog	NTSC
VESA	65" / 55": 300 x 300 50" / 43": 200 x 200	



#### Pro:Centric Smart Platform

LG's Pro:Centric Smart HTML global platform hosts system integrator partners' in-room entertainment applications with proven backward compatibility across multiple generations of webOS smart TVs. It offers one of the widest possible choices of interactive systems to our hospitality customers. Through the Pro:Centric middleware API and chromium browser, partner applications can control all aspects of the LG smart television to provide a completely unique, customizable branded user experience for hotel guests encompassing entertainment, interactive features, streaming services and digital compendiums.



# Pro:Centric Direct Hotel Management Solution from LG

The Pro:Centric Direct hotel content management solution offers simple editing tools, making it easy to perform service and IP network-based remote management with a single click. Pro:Centric Direct enables users to customize their interface easily and efficiently manage all TVs in the facility. The most recent version\* provides IoT-based in-room control as well as voice control through LG Natural Language Processing.

\* Some features may not be supported based on PCD versions.



### Pro:Idiom

DRM (digital rights management) technology unlocks access to premium content to help assure rapid and broad deployment of HDTV and other high-value digital content. DRM technology also prevents any illegal copying of content.



## Slim Depth for a Sleek Look


With a slim design, the UM670H series integrates smoothly with interiors, delivering a modern impression to your guests.



#### SoftAP

Software-enabled Access Point\* (SoftAP) is a virtual Wi-Fi feature that uses TV as a wireless hotspot, enabling guests to connect their own devices to the SoftAP.

\* Screen Share may not be operated at the same time.



#### Multi-code IR

Multi-code IR\* function eliminates any remote-control signal interaction between multiple TVs in one place. LG hospital TV supports this when used with the Multi-code IR remote control, so users can freely control their own TVs without disturbing the others.

\* Multi-code IR remote control is not provided by LG. (sold separately)



**Kensington Lock Slot** 



Reinforced Metal Stand



Lock Down Plate with Credenza Aperture


# Physical Security Features (55", 50" and 43" only)

Select LG Hotel TVs are protected by the reliable Kensington Lock solution (lock sold separately). They also come with a metal-reinforced stand to improve sturdiness, durability and safety. Finally these models include a lock-down plate with credenza aperture to lock the TV firmly to the credenza for added security.

\* Magic Motion Remote is required (sold separately)

#### CONNECTIVITY 65" / 55" / 50" / 43"


Rear



Side



#### **TECHNICAL DRAWINGS**



PECIFIC					
Category	Category	Pro:Centric Smart	Pro:Centric Smart	Pro:Centric Smart	Pro:Centric Smart
Display	Diagonal	65"	55"	50"	43"
	Resolution	3,840 x 2,160 (UHD)	3,840 x 2,160 (UHD)	3,840 x 2,160 (UHD)	3,840 x 2,160 (UHD)
	Backlight Cabinet Type	Direct	Direct	Direct	Direct
	Brightness	330 nits	330 nits	330 nits	265 nits
	Dynamic Contrast Ratio	1,000,000:1	1,000,000:1	1,000,000:1	1,000,000:1
	Static (Panel) Contrast Ratio	1,200:1	1,300:1	5,000:1	1,200:1
	Response Time	8 ms (G to G)	14 ms (G to G)	19 ms (G to G)	8 ms (G to G)
	Refresh Rate	60 Hz	60 Hz	60 Hz	60 Hz
	Life Span	30,000 Hrs.	30,000 Hrs.	30,000 Hrs.	30,000 Hrs.
Video	Al Picture Pro	Yes	Yes	Yes	Yes
	Dynamic Vivid	Yes	Yes	Yes	Yes
	HDR 10 Pro/HDR HLG	Yes / Yes	Yes / Yes	Yes / Yes	Yes / Yes
	Game Optimizer	Yes	Yes	Yes	Yes
Audio	Speaker (Sound Output)	10 W + 10 W	10 W + 10 W	10 W + 10 W	10 W + 10 W
	Speaker System	2.0 ch	2.0 ch	2.0 ch	2.0 ch
	Al Sound Pro / Al Sound	Yes	Yes	Yes	Yes
	Al Acoustic Tuning	Yes (Ready)	Yes (Ready)	Yes (Ready)	Yes (Ready)
	LG Sound Sync	Optical/Bluetooth wireless	Optical/Bluetooth wireless	Optical/Bluetooth wireless	Optical/Bluetooth wireless
Broadcasting System	Digital (Terrestrial / Cable / Satellite)	ATSC, Clear QAM	ATSC, Clear QAM	ATSC, Clear QAM	ATSC, Clear QAM
	Analog (NTSC / SECAM / PAL)	NTSC	NTSC	NTSC	NTSC
	Global IPTV Support	Yes	Yes	Yes	Yes
Hospitality	Solution Type	Pro:Centric (Smart, Cloud, Direct, V)	Pro:Centric (Smart, Cloud, Direct, V)	Pro:Centric (Smart, Cloud, Direct, V)	Pro:Centric (Smart, Cloud, Direct
	Jointion Type	Trotochare (Sinare, Groud, Bireet, 1)		Trotocheric (Sinare, Croda, Birece, V)	110.ccmine (Smart, Cloud, Direct
Solution  Smart Features	Pro:Idiom (S/W Type), (Mobile, Lite)  webOS23 User Interfa  Mobile Co	Yes ce, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2),	Yes  r Mode, Quick Access, Web Browser, SD P, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution	Yes  P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake of HDMI-CEC) (1.4), IR Out (MPI, RS-232C),	Yes ompatibility (MR18HA), on RF, WOL,
Solution	Pro:Idiom (S/W Type), (Mobile, Lite)  webOS23 User Interfa  Mobile Co Diagnostics	Yes  ce, Smart Home (Launcher Bar), Galler, SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (Mi Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Q), In emote, Moving Picture Playback (SD/HD),	Yes  / Mode, Quick Access, Web Browser, SD P, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution PI, RS-232C), HTNG-CEC (1.4), Simplink (I  ort Block, Welcome Screen (Splash Imag stant On, VLAN ID, RJP (Remote Jack Pai /Plus HD), Auto Off / Sleep Timer, Energ	Yes  P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake e HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCN ck) Compatibility (Teleadapt/Guestlink (I) y Saving Mode, Motion Eye Care, b-LAN	Yes  ompatibility (MR18HA),  on RF, WOL,  Multi-code IR  I)  HDMI-CEC),
Solution  Smart Features  Hospitality	Pro:Idiom (S/W Type), (Mobile, Lite)  webOS23 User Interfa  Mobile Co Diagnostics (  External I  Mobile Re	Yes  Cee, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (Mi  Installer Menu, Lock Mode (Limited), Po Speaker Out (R: 1.0 W, L: 1.0 W, 8 Ω), In emote, Moving Picture Playback (SD/HD), Anti-theft System (Kensington Lo	Yes  / Mode, Quick Access, Web Browser, SD p, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution pl, RS-232C), HTNG-CEC (1.4), Simplink (I ort Block, Welcome Screen (Splash Imagistant On, VLAN ID, RJP (Remote Jack Par/Plus HD), Auto Off / Sleep Timer, Energ ck, Credenza/Security Aperture (Except	Yes  P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake c HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCN ck) Compatibility (Teleadapt/Guestlink (I y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65")	Yes  ompatibility (MR18HA),  on RF, WOL,  Multi-code IR  I)  HDMI-CEC),  embedded
Solution  Smart Features  Hospitality	Pro:Idiom (S/W Type), (Mobile, Lite)  webOS23 User Interfa  Mobile Co Diagnostics	Yes  ce, Smart Home (Launcher Bar), Galler, SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MI Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Ω), In emote, Moving Picture Playback (SD/HD, Anti-theft System (Kensington Lo	Yes  / Mode, Quick Access, Web Browser, SD P, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution Pl, RS-232C), HTNG-CEC (1.4), Simplink (I  ort Block, Welcome Screen (Splash Imagstant On, VLAN ID, RJP (Remote Jack Par/Plus HD), Auto Off / Sleep Timer, Energ ck, Credenza/Security Aperture (Except In (2.0), RS-232C In (3.5 mm TRRS), Spec DMI In (2.0), USB In (2.0), Antenna/Cable	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake e HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCM ck) Compatibility (Teleadapt/Guestlink (I y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serv	Yes  Ompatibility (MR18HA),  On RF, WOL,  Multi-code IR  I)  HDMI-CEC),  embedded  ice Only (3.5 mm TRS)
Solution  Smart Features  Hospitality Features  Jack	Pro:Idiom (S/W Type), (Mobile, Lite)  webOS23 User Interfa  Mobile Co Diagnostics  External: Mobile Re  Set Side  Set Rear	Yes  ce, Smart Home (Launcher Bar), Galler, SW Clock (World Clock / Alarm), SoftAnnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MI Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1,0 W, L: 1,0 W, 8 Q), In emote, Moving Picture Playback (SD/HD, Anti-theft System (Kensington Lo  HDMI In x2 (2.0), USB	Yes  / Mode, Quick Access, Web Browser, SD P, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution Pl, RS-232C), HTNG-CEC (1.4), Simplink (I  ort Block, Welcome Screen (Splash Imagistant On, VLAN ID, RJP (Remote Jack Par/Plus HD), Auto Off / Sleep Timer, Energick, Credenza/Security Aperture (Except  In (2.0), RS-232C In (3.5 mm TRRS), Special In (2.0), USB In (2.0), Antenna/Cable-Link CFG (3.5 mm TRS) (b-LAN Service),	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake of HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCM ck) Compatibility (Teleadapt/Guestlink (I y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serve In (Dual b-LAN), Optical Digital Audio O LAN (R145), Aux LAN (R145), MPI Port (RJ	Yes  Ompatibility (MR18HA),  on RF, WOL,  Multi-code IR  I)  IDMI-CEC),  embedded  sice Only (3.5 mm TRS)  ut,  12)
Solution  Smart Features  Hospitality Features  Jack	Pro:Idiom (S/W Type), (Mobile, Lite)  webOS23 User Interfa  Mobile Co Diagnostics  External: Mobile Re  Set Side  Set Rear  VESA Compatible	Yes  ce, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MI  Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8.0), In mote, Moving Picture Playback (SD/HD), Anti-theft System (Kensington Lo  HDMI In x2 (2.0), USB  HE TV- 300 × 300 mm	Yes  / Mode, Quick Access, Web Browser, SD p, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution pl, RS-232C), HTNG-CEC (1.4), Simplink (I port Block, Welcome Screen (Splash Imagistant On, VLAN ID, RJP (Remote Jack Pai/Plus HD), Auto Off / Sleep Timer, Energ ck, Credenza/Security Aperture (Except In (2.0), RS-232C In (3.5 mm TRRS), Special In (2.0), USB In (2.0), Antenna/Cable Link CFG (3.5 mm TRS) (b-LAN Service), 300 × 300 mm	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake & HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCN ck) Compatibility (Teleadapt/Guestlink (I y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Server In (Dual b-LAN), Optical Digital Audio O LAN (RJ45), Aux LAN (RJ45), MPI Port (RJ	Yes  Ompatibility (MR18HA),  on RF, WOL,  Multi-code IR  I)  IDMI-CEC),  embedded  sice Only (3.5 mm TRS)  ut,  12)  200 × 200 mm
Solution  Smart Features  Hospitality Features  Jack	Pro:Idiom (S/W Type), (Mobile, Lite)  webOS23 User Interfa  Mobile Co Diagnostics:  External: Mobile Re  Set Side  Set Rear  VESA Compatible  Stand Type	Yes  Cee, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (Mi  Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Ω), In emote, Moving Picture Playback (SD/HD), Anti-theft System (Kensington Lo  HDMI In x2 (2.0), USB  HI TV- 300 × 300 mm  1 pole (Fixed)	Yes  / Mode, Quick Access, Web Browser, SD p, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution pl, RS-232C), HTNG-CEC (1.4), Simplink (I prt Block, Welcome Screen (Splash Imagistant On, VLAN ID, RJP (Remote Jack Par/Plus HD), Auto Off / Sleep Timer, Energick, Credenza/Security Aperture (Except In (2.0), RS-232C In (3.5 mm TRRS), Spei DMI In (2.0), USB In (2.0), Antenna/Cable Link CFG (3.5 mm TRS) (b-LAN Service), 300 x 300 mm 1 pole (Swivel)	Yes  P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake c HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCN ck) Compatibility (Teleadapt/Guestlink (I y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serv et In (Dual b-LAN), Optical Digital Audio O LAN (RJ45), Aux LAN (RJ45), MPI Port (RJ 200 × 200 mm 1 pole (Swivel)	Yes  ompatibility (MR18HA), on RF, WOL, Multi-code IR  I) IDMI-CEC), embedded  sice Only (3.5 mm TRS)  ut, 12)  200 × 200 mm 1 pole (Swivel)
Solution  Smart Features  Hospitality Features  Jack	Pro:Idiom (S/W Type), (Mobile, Lite)  webOS23 User Interfa  Mobile Co Diagnostics  External: Mobile Re  Set Side  Set Rear  VESA Compatible  Stand Type  Front Color	Yes  ce, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MI  Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Ω), In mote, Moving Picture Playback (SD/HD), Anti-theft System (Kensington Lo  HDMI In x2 (2.0), USB  HC TV- 300 × 300 mm  1 pole (Fixed)  Dark Charcoal Gray	Yes  / Mode, Quick Access, Web Browser, SD p, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution Pl, RS-232C), HTNG-CEC (1.4), Simplink (I  ort Block, Welcome Screen (Splash Imagestant On, VLAN ID, RJP (Remote Jack Par/Plus HD), Auto Off / Sleep Timer, Energ ck, Credenza/Security Aperture (Except  In (2.0), RS-232C In (3.5 mm TRRS), Special In (2.0), USB In (2.0), Antenna/Cable Link CFG (3.5 mm TRS) (b-LAN Service),  300 × 300 mm  1 pole (Swivel)  Dark Charcoal Gray	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake c HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCN ck) Compatibility (Teleadapt/Guestlink (I y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serv el In (Dual b-LAN), Optical Digital Audio O LAN (RJ45), Aux LAN (RJ45), MPI Port (RJ 200 × 200 mm  1 pole (Swivel) Dark Charcoal Gray	Yes  ompatibility (MR18HA), on RF, WOL, Multi-code IR  I) IOMI-CEC), embedded  sice Only (3.5 mm TRS)  ut, 12)  200 × 200 mm  1 pole (Swivel)  Dark Charcoal Gray
Solution  Smart Features  Hospitality Features  Jack	Pro:Idiom (S/W Type), (Mobile, Lite)  webOS23 User Interfa  Mobile Co Diagnostics:  External: Mobile Re  Set Side  Set Rear  VESA Compatible  Stand Type	Yes  Cee, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (Mi  Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Ω), In emote, Moving Picture Playback (SD/HD), Anti-theft System (Kensington Lo  HDMI In x2 (2.0), USB  HI TV- 300 × 300 mm  1 pole (Fixed)	Yes  / Mode, Quick Access, Web Browser, SD p, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution pl, RS-232C), HTNG-CEC (1.4), Simplink (I prt Block, Welcome Screen (Splash Imagistant On, VLAN ID, RJP (Remote Jack Par/Plus HD), Auto Off / Sleep Timer, Energick, Credenza/Security Aperture (Except In (2.0), RS-232C In (3.5 mm TRRS), Spei DMI In (2.0), USB In (2.0), Antenna/Cable Link CFG (3.5 mm TRS) (b-LAN Service), 300 x 300 mm 1 pole (Swivel)	Yes  P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake c HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCN ck) Compatibility (Teleadapt/Guestlink (I y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serv et In (Dual b-LAN), Optical Digital Audio O LAN (RJ45), Aux LAN (RJ45), MPI Port (RJ 200 × 200 mm 1 pole (Swivel)	Yes  ompatibility (MR18HA), on RF, WOL, Multi-code IR  I) IDMI-CEC), embedded  sice Only (3.5 mm TRS)  ut, 12)  200 × 200 mm 1 pole (Swivel)
Solution  Smart Features  Hospitality Features  Jack	Pro:Idiom (S/W Type), (Mobile, Lite)  webOS23 User Interfa  Mobile Co Diagnostics:  External: Mobile Re  Set Side  Set Rear  VESA Compatible  Stand Type  Front Color Dimensions without Stand (W x H x D) Dimensions with Stand	Yes  Cee, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (Mi  Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Ω), In emote, Moving Picture Playback (SD/HD), Anti-theft System (Kensington Lo  HDMI In x2 (2.0), USB  HI  TV-  300 × 300 mm  1 pole (Fixed)  Dark Charcoal Gray  57.2 x 33 x 2.3 in. 1,454 × 838 × 57.7 mm  57.2 x 35.8 x 13.4 in.	Yes  / Mode, Quick Access, Web Browser, SD p, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution Pl, RS-232C), HTNG-CEC (1.4), Simplink (I  ort Block, Welcome Screen (Splash Imagistant On, VLAN ID, RJP (Remote Jack Par /Plus HD), Auto Off / Sleep Timer, Energ ck, Credenza/Security Aperture (Except  In (2.0), RS-232C In (3.5 mm TRRS), Spei  OMI In (2.0), USB In (2.0), Antenna/Cable Link CFG (3.5 mm TRS) (b-LAN Service),  300 x 300 mm  1 pole (Swivel)  Dark Charcoal Gray 48.6 x 28.1 x 2.3 in. 1,235 x 715 x 57.5 mm  48.6 x 30.6 x 11.9 in.	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake c HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCN ck) Compatibility (Teleadapt/Guestlink (I y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serv et In (Dual b-LAN), Optical Digital Audio O LAN (RJ45), Aux LAN (RJ45), MPI Port (RJ 200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray 44.1 × 25.6 × 2.2 in. 1,121 × 651 × 57.1 mm 44.1 × 28.1 × 11.9 in.	Yes  ompatibility (MR18HA), on RF, WOL, Multi-code IR  I)  IDMI-CEC), embedded  ice Only (3.5 mm TRS)  ut, 12)  200 × 200 mm  1 pole (Swivel)  Dark Charcoal Gray 38.1 × 22.2 × 2.2 in. 967 × 564 × 57.1 mm 38.1 × 24.5 × 11.9 in.
Solution  Smart Features  Hospitality Features  Jack	Pro:Idiom (S/W Type), (Mobile, Lite)  webOS23 User Interfa  Mobile Co Diagnostics (  External : Mobile Re  Set Side  Set Rear  VESA Compatible  Stand Type  Front Color  Dimensions without Stand (W x H x D) Dimensions with Stand (W x H x D) Shipping Dimensions	Yes  ce, Smart Home (Launcher Bar), Galler, SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MI Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Ω), In mote, Moving Picture Playback (SD/HD Anti-theft System (Kensington Lo HDMI In x2 (2.0), USB HI TV-300 x 300 mm  1 pole (Fixed)  Dark Charcoal Gray 57.2 x 33 x 2.3 in. 1,454 x 838 x 57.7 mm	Yes  / Mode, Quick Access, Web Browser, SD P, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution Pl, RS-232C), HTNG-CEC (1.4), Simplink (I  ort Block, Welcome Screen (Splash Imagstant On, VLAN ID, RJP (Remote Jack Par/Plus HD), Auto Off / Sleep Timer, Energ ck, Credenza/Security Aperture (Except  In (2.0), RS-232C In (3.5 mm TRRS), Special In (2.0), USB In (2.0), Antenna/Cable Link CFG (3.5 mm TRS) (b-LAN Service), 300 × 300 mm  1 pole (Swivel)  Dark Charcoal Gray 48.6 × 28.1 × 2.3 in. 1,235 × 715 × 57.5 mm	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake e HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCM ck) Compatibility (Teleadapt/Guestlink (I y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65")  aker Out/Line Out (3.5 mm Stereo), Serv et In (Dual b-LAN), Optical Digital Audio O LAN (RJ45), Aux LAN (RJ45), MPI Port (RJ 200 × 200 mm  1 pole (Swivel)  Dark Charcoal Gray 44.1 × 25.6 × 2.2 in. 1,121 × 651 × 57.1 mm	Yes  Ompatibility (MR18HA),  on RF, WOL, Multi-code IR  I) HDMI-CEC), embedded  ice Only (3.5 mm TRS)  ut, 12)  200 × 200 mm  1 pole (Swivel)  Dark Charcoal Gray  38.1 × 22.2 × 2.2 in. 967 × 564 × 57.1 mm
Solution  Smart Features  Hospitality Features  Jack Interface	Pro:Idiom (S/W Type), (Mobile, Lite)  webOS23 User Interfate Mobile Conception of Diagnostics of Mobile Researed Profits of Mobile Research Profits of Mobil	Yes  ce, Smart Home (Launcher Bar), Galler, SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MI Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Ω), In mote, Moving Picture Playback (SD/HD, Anti-theft System (Kensington Lo HDMI In x2 (2.0), USB  HDMI In x2 (2.0), USB  HI TV:  300 × 300 mm  1 pole (Fixed)  Dark Charcoal Gray  57.2 × 33 × 2.3 in. 1,454 × 838 × 57.7 mm  57.2 × 35.8 × 13.4 in. 1,454 × 909 × 340 mm 63 × 38.2 × 9 in. 1,600 × 970 × 228 mm	Yes  / Mode, Quick Access, Web Browser, SD P, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution Pl, RS-232C), HTNG-CEC (1.4), Simplink (I  ort Block, Welcome Screen (Splash Imagstant On, VLAN ID, RJP (Remote Jack Par/Plus HD), Auto Off / Sleep Timer, Energ ck, Credenza/Security Aperture (Except  In (2.0), RS-232C In (3.5 mm TRRS), Special Specia	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake of HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCM ck) Compatibility (Teleadapt/Guestlink (IV y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65")  aker Out/Line Out (3.5 mm Stereo), Serv e In (Dual b-LAN), Optical Digital Audio O LAN (RJ45), Aux LAN (RJ45), MPI Port (RJ 200 × 200 mm  1 pole (Swivel)  Dark Charcoal Gray 44.1 × 25.6 × 2.2 in. 1,121 × 651 × 57.1 mm 44.1 × 28.1 × 11.9 in. 1,121 × 713 × 303 mm 51.9 × 31.9 × 7.4 in. 1,317 × 810 × 188 mm	Yes  Ompatibility (MR18HA),  on RF, WOL, Multi-code IR  I)  HDMI-CEC), embedded  ice Only (3.5 mm TRS)  ut, 12)  200 × 200 mm  1 pole (Swivel)  Dark Charcoal Gray 38.1 × 24.2 × 2.2 in. 967 × 564 × 57.1 mm 38.1 × 24.5 × 11.9 in. 967 × 623 × 303 mm 42.3 × 26× 8.0 in. 1,075 × 660 × 203 mm
Solution  Smart Features  Hospitality Features  Jack Interface	Pro:Idiom (S/W Type), (Mobile, Lite)  webOS23 User Interfa  Mobile Co Diagnostics (  External: Mobile Re  Set Side  Set Rear  VESA Compatible  Stand Type  Front Color  Dimensions without Stand (W x H x D)  Shipping Dimensions (W x H x D)  Weight without Stand  Weight without Stand	Yes  ce, Smart Home (Launcher Bar), Galler, SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MI Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Ω), Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Ω), Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Ω), Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, E. 1.0 W, 8 Ω), Installer Moving Picture Playback (SD/HD, Anti-theft System (Kensington Lo HDMI In x2 (2.0), USB  HDMI In x2 (2.0), USB  HIT TV:  300 × 300 mm  1 pole (Fixed)  Dark Charcoal Gray  57.2 × 33 × 2.3 in. 1,454 × 838 × 57.7 mm  57.2 × 35.8 × 13.4 in. 1,454 × 909 × 340 mm  63 × 38.2 × 9 in. 1,600 × 970 × 228 mm  47.4 lbs. / 21.5 kg	Yes  / Mode, Quick Access, Web Browser, SD P, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution PI, RS-232C), HTNG-CEC (1.4), Simplink (I  ort Block, Welcome Screen (Splash Imagstant On, VLAN ID, RJP (Remote Jack Par (Plus HD), Auto Off / Sleep Timer, Energ ck, Credenza/Security Aperture (Except  In (2.0), RS-232C In (3.5 mm TRRS), Speca  OMI In (2.0), USB In (2.0), Antenna/Cable Link CFG (3.5 mm TRS) (b-LAN Service),  300 × 300 mm  1 pole (Swivel)  Dark Charcoal Gray  48.6 × 28.1 × 2.3 in. 1,235 × 715 × 57.5 mm  48.6 × 30.6 × 11.9 in. 1,235 × 777 × 303 mm  53.5 × 33.9 × 8.1 in. 1,360 × 860 × 207 mm  30.9 lbs. / 14.0 kg	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, J, IoT, EZ-Manager, USB Cloning, Wake c HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e). Insert Image, One Channel Map (LCM ck) Compatibility (Teleadapt/Guestlink (Iy Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65")  aker Out/Line Out (3.5 mm Stereo), Serven In (Dual b-LAN), Optical Digital Audio O LAN (RJ45), Aux LAN (RJ45), MPI Port (RJ 200 × 200 mm 1 pole (Swivel)  Dark Charcoal Gray 44.1 × 25.6 × 2.2 in. 1,121 × 651 × 57.1 mm 44.1 × 28.1 × 11.9 in. 1,121 × 713 × 303 mm 51.9 × 31.9 × 7.4 in. 1,317 × 810 × 188 mm 26.7 lbs. / 12.1 kg	Yes  Ompatibility (MR18HA),  on RF, WOL,  Multi-code IR  I)  HDMI-CEC),  embedded  ice Only (3.5 mm TRS)  ut,  12)  200 × 200 mm  1 pole (Swivel)  Dark Charcoal Gray  38.1 × 22.2 × 2.2 in.  967 × 564 × 57.1 mm  38.1 × 24.5 × 11.9 in.  967 × 623 × 303 mm  42.3 × 26 × 8.0 in.  1,075 × 660 × 203 mm  19.4 lbs. / 8.8 kg
Solution  Smart Features  Hospitality Features  Jack Interface	Pro:Idiom (S/W Type), (Mobile, Lite)  webOS23 User Interfa  Mobile Co Diagnostics of the Company of the Color of the Company o	Yes  ce, Smart Home (Launcher Bar), Galler, SW Clock (World Clock / Alarm), SoftAnnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MI Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Q), In mote, Moving Picture Playback (SD/HD, Anti-theft System (Kensington Lo HDMI In x2 (2.0), USB  HT TV:  300 × 300 mm  1 pole (Fixed)  Dark Charcoal Gray  57.2 × 33. × 2.3 in. 1,454 × 838 × 57.7 mm  57.2 × 35.8 × 13.4 in. 1,454 × 909 × 340 mm  63 × 38.2 × 9 in. 1,600 × 970 × 228 mm  47.4 lbs. / 21.5 kg  50.5 lbs. / 22.9 kg	Yes  / Mode, Quick Access, Web Browser, SD P, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution Pl, RS-232C), HTNG-CEC (1.4), Simplink (I  ort Block, Welcome Screen (Splash Imagestant On, VLAN ID, RIP (Remote Jack Par/Plus HD), Auto Off / Sleep Timer, Energick, Credenza/Security Aperture (Except  In (2.0), RS-232C In (3.5 mm TRRS), Special Stanton (Splash Imagestant On, VLAN ID, RIP (Remote Jack Par/Plus HD), Auto Off / Sleep Timer, Energick, Credenza/Security Aperture (Except  In (2.0), RS-232C In (3.5 mm TRRS), Special Splash In (2.0), Antenna/Cable-Link CFG (3.5 mm TRS) (b-LAN Service),  300 × 300 mm  1 pole (Swivel)  Dark Charcoal Gray  48.6 × 28.1 × 2.3 in. 1,235 × 715 × 57.5 mm 48.6 × 30.6 × 11.9 in. 1,235 × 777 × 303 mm 53.5 × 33.9 × 8.1 in. 1,360 × 860 × 207 mm 30.9 lbs. / 14.0 kg 37.9 lbs. / 17.2 kg	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake of HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCM ck) Compatibility (Teleadapt/Guestlink (I y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serve In (Dual b-LAN), Optical Digital Audio O LAN (R145), Aux LAN (R145), MPI Port (R1 200 × 200 mm 1 pole (Swivel)  Dark Charcoal Gray 44.1 × 25.6 × 2.2 in. 1,121 × 651 × 57.1 mm 44.1 × 28.1 × 11.9 in. 1,121 × 713 × 303 mm 51.9 × 31.9 × 7.4 in. 1,317 × 810 × 188 mm 26.7 lbs. / 12.1 kg 33.7 lbs. / 15.3 kg	Yes  Ompatibility (MR18HA),  on RF, WOL,  Multi-code IR  I)  I)  IDMI-CEC),  embedded  ice Only (3.5 mm TRS)  ut,  12)  200 × 200 mm  1 pole (Swivel)  Dark Charcoal Gray  38.1 × 22.2 × 2.2 in.  967 × 564 × 57.1 mm  38.1 × 24.5 × 11.9 in.  967 × 623 × 303 mm  42.3 × 268 8.0 in.  1,075 × 660 × 203 mm  19.4 lbs. / 8.8 kg  26.5 lbs. / 12.0 kg
Solution  Smart Features  Hospitality Features  Jack Interface	Pro:Idiom (S/W Type), (Mobile, Lite)  webOS23 User Interfa  Mobile Co Diagnostics  External: Mobile Re  Set Side  Set Rear  VESA Compatible  Stand Type  Front Color  Dimensions without Stand (W x H x D)  Dimensions with Stand (W x H x D)  Shipping Dimensions (W x H x D)  Weight without Stand  Weight with Stand  Weight with Stand  Shipping Weight	Cee, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftAnnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MI Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1,0 W, L: 1,0 W, 8 Q), In mote, Moving Picture Playback (SD/HD, Anti-theft System (Kensington Lo HDMI In x2 (2.0), USB HIT TV:  300 × 300 mm  1 pole (Fixed)  Dark Charcoal Gray  57.2 × 33.8 × 37.7 mm  57.2 × 35.8 × 13.4 in. 1,454 × 909 × 340 mm 63 × 38.2 × 9in. 1,600 × 970 × 228 mm 47.4 lbs. / 21.5 kg 50.5 lbs. / 22.9 kg	Yes  / Mode, Quick Access, Web Browser, SD p, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution pl, RS-232C), HTNG-CEC (1.4), Simplink (I  ort Block, Welcome Screen (Splash Imagistant On, VLAN ID, RIP (Remote Jack Par/Plus HD), Auto Off / Sleep Timer, Energick, Credenza/Security Aperture (Except  In (2.0), RS-232C In (3.5 mm TRRS), Special Standard (Special Standard Security Aperture)  DMI In (2.0), USB In (2.0), Antenna/Cable-Link CFG (3.5 mm TRS) (b-LAN Service),  300 x 300 mm  1 pole (Swivel)  Dark Charcoal Gray  48.6 x 28.1 x 2.3 in. 1,235 x 715 x 57.5 mm  48.6 x 30.6 x 11.9 in. 1,235 x 777 x 303 mm 53.5 x 33.9 x 8.1 in. 1,360 x 860 x 207 mm 30.9 lbs. / 14.0 kg 37.9 lbs. / 17.2 kg 49.2 lbs. / 22.3 kg	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake of HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCN ck) Compatibility (Teleadapt/Guestlink (I y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serven (In (Dual b-LAN), Optical Digital Audio O LAN (R145), Aux LAN (R145), MPI Port (R1 200 × 200 mm 1 pole (Swivel)  Dark Charcoal Gray 44.1 × 25.6 × 2.2 in. 1,121 × 651 × 57.1 mm 44.1 × 28.1 × 11.9 in. 1,121 × 713 × 303 mm 51.9 × 31.9 × 7.4 in. 1,317 × 810 × 188 mm 26.7 lbs. / 12.1 kg 33.7 lbs. / 15.3 kg 41.0 lbs. / 18.6 kg	Yes  Ompatibility (MR18HA),  on RF, WOL,  Multi-code IR  I)  IDMI-CEC),  embedded  dice Only (3.5 mm TRS)  ut,  12)  200 × 200 mm  1 pole (Swivel)  Dark Charcoal Gray  38.1 × 22.2 × 2.2 in.  967 × 564 × 57.1 mm  38.1 × 24.5 × 11.9 in.  967 × 623 × 303 mm  42.3 × 26 × 8.0 in.  1,075 × 660 × 203 mm  19.4 lbs. / 8.8 kg  26.5 lbs. / 12.0 kg  34.0 lbs. / 15.4 kg
Solution  Smart Features  Hospitality Features  Jack Interface	Pro:Idiom (S/W Type), (Mobile, Lite)  webOS23 User Interfa  Mobile Co Diagnostics  External: Mobile Re  Set Side  Set Rear  VESA Compatible  Stand Type  Front Color  Dimensions without Stand (W x H x D) Dimensions with Stand (W x H x D) Shipping Dimensions (W x H x D) Weight without Stand Weight with Stand Shipping Weight On Bezel Width (L/R/U/B)	Cee, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftAnnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MI Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8.0), In mote, Moving Picture Playback (SD/HD), Anti-theft System (Kensington Lock HDMI In x2 (2.0), USB HDMI In x2 (2.0), US	Yes  / Mode, Quick Access, Web Browser, SD p, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution pl, RS-232C), HTNG-CEC (1.4), Simplink (I port Block, Welcome Screen (Splash Imagestant On, VLAN ID, RJP (Remote Jack Par/Plus HD), Auto Off / Sleep Timer, Energick, Credenza/Security Aperture (Except  In (2.0), RS-232C In (3.5 mm TRS), Special Stant Off (3.5 mm TRS), Special Stant Off (3.5 mm TRS), Special Stant Off (3.5 mm TRS), (b-LAN Service),  300 x 300 mm  1 pole (Swivel)  Dark Charcoal Gray 48.6 x 28.1 x 2.3 in. 1,235 x 717 x 303 mm 48.6 x 30.6 x 11.9 in. 1,235 x 777 x 303 mm 53.5 x 33.9 x 8.1 in. 1,360 x 860 x 207 mm 30.9 lbs. / 14.0 kg 37.9 lbs. / 17.2 kg 49.2 lbs. / 22.3 kg 12.8 / 12.8 / 12.8 / 19.9 mm	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, J. IoT, EZ-Manager, USB Cloning, Wake of HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCN ck) Compatibility (Teleadapt/Guestlink (I y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Servel In (Dual b-LAN), Optical Digital Audio O LAN (RJ45), Aux LAN (RJ45), MPI Port (RJ 200 x 200 mm 1 pole (Swivel)  Dark Charcoal Gray 44.1 x 25.6 x 2.2 in. 1,211 x 651 x 57.1 mm 44.1 x 28.1 x 11.9 in. 1,121 x 713 x 303 mm 51.9 x 31.9 x 7.4 in. 1,317 x 810 x 188 mm 26.7 lbs. / 12.1 kg 33.7 lbs. / 15.3 kg 41.0 lbs. / 18.6 kg 12.8 / 12.8 / 12.8 / 19.9 mm	Yes  Ompatibility (MR18HA),  on RF, WOL,  Multi-code IR  I)  IDMI-CEC),  embedded  dice Only (3.5 mm TRS)  ut,  12)  200 × 200 mm  1 pole (Swivel)  Dark Charcoal Gray  38.1 × 22.2 × 2.2 in.  967 × 564 × 57.1 mm  38.1 × 24.5 × 11.9 in.  967 × 623 × 303 mm  42.3 × 26 × 8.0 in.  1,075 × 660 × 203 mm  19.4 lbs. / 8.8 kg  26.5 lbs. / 12.0 kg  34.0 lbs. / 15.4 kg  12.8 / 12.8 / 12.8 / 19.9 mm
Solution  Smart Features  Hospitality Features  Jack Interface	Pro:Idiom (S/W Type), (Mobile, Lite)  webOS23 User Interfa  Mobile Co Diagnostics:  External: Mobile Re  Set Side  Set Rear  VESA Compatible  Stand Type  Front Color Dimensions without Stand (W x H x D) Dimensions with Stand (W x H x D) Shipping Dimensions (W x H x D) Weight without Stand Weight with Stand Weight with Stand Shipping Weight On Bezel Width (L/R/U/B)	Yes  ce, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftAnnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MI Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8.0), In emote, Moving Picture Playback (SD/HD), Anti-theft System (Kensington Lock) HDMI In x2 (2.0), USB  HI TV-  300 × 300 mm  1 pole (Fixed)  Dark Charcoal Gray  57.2 × 33.2 × 3in.  1,454 × 838 × 57.7 mm  57.2 × 35.8 × 13.4 in.  1,454 × 909 × 340 mm  63 × 38.2 × 9in.  1,600 × 970 × 228 mm  47.4 lbs. / 21.5 kg  50.5 lbs. / 22.9 kg  63.7 lbs. / 28.9 kg  12.8 / 12.8 / 12.8 / 19.9 mm  6.8 / 6.8 / 6.8 / 18.4 mm	Yes  / Mode, Quick Access, Web Browser, SD p, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution) P, RS-232C), HTNG-CEC (1.4), Simplink (I port Block, Welcome Screen (Splash Imagistant On, VLAN ID, RJP (Remote Jack Par P(Plus HD), Auto Off / Sleep Timer, Energ ck, Credenza/Security Aperture (Except In (2.0), RS-232C In (3.5 mm TRRS), Spei DMI In (2.0), USB In (2.0), Antenna/Cable Link CFG (3.5 mm TRS) (b-LAN Service),  300 × 300 mm  1 pole (Swivel)  Dark Charcoal Gray 48.6 × 20.5 × 15.5 mm 48.6 × 30.6 × 11.9 in. 1,235 × 715 × 57.5 mm 48.6 × 30.6 × 11.9 in. 1,235 × 733.9 × 8.1 in. 1,360 × 860 × 207 mm 30.9 lbs. / 14.0 kg 37.9 lbs. / 17.2 kg 49.2 lbs. / 22.3 kg 12.8 / 12.8 / 12.8 / 19.9 mm 6.9 / 6.9 / 6.9 / 18.4 mm	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake & HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCN ck) Compatibility (Teleadapt/Guestlink (I y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Server In (Dual b-LAN), Optical Digital Audio O LAN (RJ45), Aux LAN (RJ45), MPI Port (RJ 200 × 200 mm 1 pole (Swivel)  Dark Charcoal Gray 44.1 × 25.6 × 2.2 in. 1,121 × 651 × 57.1 mm 44.1 × 28.1 × 11.9 in. 1,121 × 713 × 303 mm 51.9 × 74 in. 1,317 × 810 × 188 mm 26.7 lbs. / 12.1 kg 33.7 lbs. / 15.3 kg 41.0 lbs. / 18.6 kg 12.8 / 12.8 / 19.9 mm 7.3 / 7.3 / 7.8 / 18.4 mm	Yes  Ompatibility (MR18HA),  On RF, WOL,  Multi-code IR  I)  IDMI-CEC),  embedded  Ice Only (3.5 mm TRS)  ut,  12)  200 × 200 mm  1 pole (Swivel)  Dark Charcoal Gray  38.1 x 22.2 x 2.2 in.  967 × 564 × 57.1 mm  38.1 x 24.5 x 11.9 in.  967 x 623 × 303 mm  42.3 x 26 × 8.0 in.  1,075 × 660 × 203 mm  19.4 lbs. / 8.8 kg  26.5 lbs. / 12.0 kg  34.0 lbs. / 15.4 kg  12.8 / 12.8 / 19.9 mm  6.9 / 6.9 / 6.9 / 6.9 / 18.4 mm
Solution  Smart Features  Hospitality Features  Jack Interface	Pro:Idiom (S/W Type), (Mobile, Lite)  webOS23 User Interfa  Mobile Co Diagnostics:  External: Mobile Re  Set Side  Set Rear  VESA Compatible  Stand Type  Front Color Dimensions without Stand (W x H x D) Dimensions with Stand (W x H x D) Shipping Dimensions (W x H x D) Weight without Stand Weight with Stand Shipping Weight On Bezel Width (L/R/U/B) Power Supply (Voltage, Hz)	Yes  ce, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MI Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8.0), In emote, Moving Picture Playback (SD/HD), Anti-theft System (Kensington Lock)  HDMI In x2 (2.0), USB  HITTV-  300 × 300 mm  1 pole (Fixed)  Dark Charcoal Gray  57.2 × 33 × 2.3 in. 1,454 × 838 × 57.7 mm  57.2 × 35.8 × 13.4 in. 1,454 × 909 × 340 mm  63 × 38.2 × 9 in. 1,600 × 970 × 228 mm  47.4 lbs. / 21.5 kg  50.5 lbs. / 22.9 kg  63.7 lbs. / 28.9 kg  12.8 / 12.8 / 19.9 mm  6.8 / 6.8 / 6.8 / 18.4 mm  100-240 Vac, 50/60 Hz	Yes  / Mode, Quick Access, Web Browser, SD p, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution) P, RS-232C), HTNG-CEC (1.4), Simplink (I port Block, Welcome Screen (Splash Imagistant On, VLAN ID, RJP (Remote Jack Par/Plus HD), Auto Off / Sleep Timer, Energick, Credenza/Security Aperture (Except  In (2.0), RS-232C In (3.5 mm TRRS), Speitor, Credenza/Security Aperture (Except  In (2.0), RS-232C In (3.5 mm TRRS), Speitor, Sp	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, ), IoT, EZ-Manager, USB Cloning, Wake & HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCN ck) Compatibility (Teleadapt/Guestlink (I y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Server In (Dual b-LAN), Optical Digital Audio O LAN (RJ45), Aux LAN (RJ45), MPI Port (RJ 200 × 200 mm 1 pole (Swivel)  Dark Charcoal Gray 44.1 × 25.6 × 2.2 in. 1,121 × 651 × 57.1 mm 44.1 × 28.1 × 11.9 in. 1,121 × 713 × 303 mm 51.9 × 7.4 in. 1,317 × 810 × 188 mm 26.7 lbs. / 12.1 kg 33.7 lbs. / 15.3 kg 41.0 lbs. / 18.6 kg 12.8 / 12.8 / 19.9 mm 7.3 / 7.3 / 7.8 / 18.4 mm 100-240 Vac, 50/60 Hz	Yes  ompatibility (MR18HA), on RF, WOL, Multi-code IR  I)  IDMI-CEC), embedded  ice Only (3.5 mm TRS)  ut, 12)  200 × 200 mm  1 pole (Swivel)  Dark Charcoal Gray  38.1 × 22.2 × 2.2 in. 967 × 564 × 57.1 mm  38.1 × 24.5 × 11.9 in. 967 × 623 × 303 mm  42.3 × 26 × 8.0 in. 1,075 × 660 × 203 mm  19.4 lbs. / 8.8 kg  26.5 lbs. / 12.0 kg  34.0 lbs. / 15.4 kg  12.8 / 12.8 / 12.8 / 19.9 mm  6.9 / 6.9 / 6.9 / 18.4 mm  100-240 Vac, 50/60 Hz
Solution  Smart Features  Hospitality Features  Jack Interface	Pro:Idiom (S/W Type), (Mobile, Lite)  webOS23 User Interfa  Mobile Co Diagnostics:  External: Mobile Re  Set Side  Set Rear  VESA Compatible  Stand Type  Front Color Dimensions without Stand (W x H x D) Dimensions with Stand (W x H x D) Weight without Stand Weight without Stand Weight without Stand Weight with Stand Shipping Dimensions (W x H x D)  Weight without Stand Weight with Stand Shipping Weight On Bezel Width (L/R/U/B) Off Bezel Width (L/R/U/B) Power Supply (Voltage, Hz) Power Consumption (Typ. / Max.)	Cee, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftAnnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (Minstaller Menu, Lock Mode (Limited), Pospeaker Out (R: 1.0 W, L: 1.0 W, B. Q), Insemote, Moving Picture Playback (SD/HD), Anti-theft System (Kensington Lock) HDMI In x2 (2.0), USB HDMI In x2 (2.0), US	Yes  / Mode, Quick Access, Web Browser, SD p, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution Pl, RS-232C), HTNG-CEC (1.4), Simplink (I  ort Block, Welcome Screen (Splash Imagistant On, VLAN ID, RJP (Remote Jack Par/Plus HD), Auto Off / Sleep Timer, Energ ck, Credenza/Security Aperture (Except  In (2.0), RS-232C In (3.5 mm TRRS), Spei  OMI In (2.0), USB In (2.0), Antenna/Cable Link CFG (3.5 mm TRS) (b-LAN Service),  300 × 300 mm  1 pole (Swivel)  Dark Charcoal Gray 48.6 × 30.6 × 11.9 in. 1,235 × 715 × 57.5 mm 48.6 × 30.6 × 11.9 in. 1,235 × 777 × 303 mm 53.5 × 33.9 × 38.1 in. 1,360 × 860 × 207 mm 30.9 lbs. / 14.0 kg 37.9 lbs. / 17.2 kg 49.2 lbs. / 22.3 kg 12.8 / 12.8 / 12.8 / 19.9 mm 6.9 / 6.9 / 6.9 / 18.4 mm 100-240 Vac, 50/60 Hz 135 W / 163 W	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, J. IoT, EZ-Manager, USB Cloning, Wake & HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCN ck) Compatibility (Teleadapt/Guestlink (I y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Server In (Dual b-LAN), Optical Digital Audio O LAN (RI45), Aux LAN (RI45), MPI Port (RI 200 × 200 mm 1 pole (Swivel)  Dark Charcoal Gray 44.1 x 25.6 x 2.2 in. 1,121 x 651 x 57.1 mm 44.1 x 28.1 x 11.9 in. 1,121 x 713 x 303 mm 51.9 x 31.9 x 7.4 in. 1,317 x 810 x 188 mm 26.7 lbs. /12.1 kg 33.7 lbs. /15.3 kg 41.0 lbs. /18.6 kg 12.8 / 12.8 / 12.8 / 19.9 mm 7.3 / 7.3 / 7.8 / 18.4 mm 100-240 Vac, 50/60 Hz 112 W / 135 W	Yes  Ompatibility (MR18HA),  On RF, WOL,  Multi-code IR  I)  IDMI-CEC),  embedded  Ice Only (3.5 mm TRS)  ut,  12)  200 × 200 mm  1 pole (Swivel)  Dark Charcoal Gray  38.1 × 22.2 × 2.2 in.  967 × 564 × 57.1 mm  38.1 × 24.5 × 11.9 in.  967 × 663 × 303 mm  42.3 × 26 × 8.0 in.  1,075 × 660 × 203 mm  19.4 lbs. / 8.8 kg  26.5 lbs. / 12.0 kg  34.0 lbs. / 15.4 kg  12.8 / 12.8 / 12.8 / 19.9 mm  6.9 / 6.9 / 6.9 / 18.4 mm  100-240 Vac, 50/60 Hz  82 W / 119 W
Solution  Smart Features  Hospitality Features  Jack Interface	Pro:Idiom (S/W Type), (Mobile, Lite)  webOS23 User Interfa  Mobile Co Diagnostics I  External: Mobile Re  Set Side  Set Rear  VESA Compatible  Stand Type  Front Color  Dimensions without Stand (Wx H x D) Dimensions without Stand (Wx H x D)  Shipping Dimensions (Wx H x D)  Weight without Stand  Weight with Stand  Shipping Weight  On Bezel Width (L/R/U/B)  Off Bezel Width (L/R/U/B)  Power Consumption (Typ. / Max.)  Standby Power Consumption	Yes  ce, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (Minstaller Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, B. Q), In gemote, Moving Picture Playback (SD/HD), Anti-theft System (Kensington Lower HDMI In x2 (2.0), USB HDMI In x2 (2	Yes  / Mode, Quick Access, Web Browser, SD p, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution Pl, RS-232C), HTNG-CEC (1.4), Simplink (I  ort Block, Welcome Screen (Splash Imagistant On, VLAN ID, RJP (Remote Jack Par) P(Plus HD), Auto Off / Sleep Timer, Energick, Credenza/Security Aperture (Except  In (2.0), RS-232C In (3.5 mm TRRS), Spei  DMI In (2.0), USB In (2.0), Antenna/Cable Link CFG (3.5 mm TRS) (b-LAN Service),  300 × 300 mm  1 pole (Swivel)  Dark Charcoal Gray  48.6 × 30.6 × 11.9 in. 1,235 × 715 × 57.5 mm 48.6 × 30.6 × 11.9 in. 1,235 × 777 × 303 mm 53.5 × 33.9 × 8.1 in. 1,360 × 860 × 207 mm 30.9 lbs. / 14.0 kg 37.9 lbs. / 17.2 kg 49.2 lbs. / 22.3 kg 12.8 / 12.8 / 19.9 mm 6.9 / 6.9 / 6.9 / 18.4 mm 100-240 Vac, 50/60 Hz 135 W / 163 W Under 0.5 W	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, J. IoT, EZ-Manager, USB Cloning, Wake & HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCN ck) Compatibility (Teleadapt/Guestlink (I y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Server In (Dual b-LAN), Optical Digital Audio O LAN (RJ45), Aux LAN (RJ45), MPI Port (RJ 200 × 200 mm 1 pole (Swivel)  Dark Charcoal Gray 44.1 x 25.6 x 2.2 in. 1,121 x 651 x 57.1 mm 44.1 x 28.1 x 11.9 in. 1,121 x 713 x 303 mm 51.9 x 319 x 7.4 in. 1,317 x 810 x 188 mm 26.7 lbs. /12.1 kg 33.7 lbs. /15.3 kg 41.0 lbs. /18.6 kg 12.8 / 12.8 / 12.8 / 19.9 mm 7.3 / 7.3 / 7.8 / 18.4 mm 100-240 Vac, 50/60 Hz 112 W / 135 W Under 0.5 W	Yes  ompatibility (MR18HA), on RF, WOL, Multi-code IR  I)  IDMI-CEC), embedded  ice Only (3.5 mm TRS)  ut, 12)  200 × 200 mm  1 pole (Swivel)  Dark Charcoal Gray  38.1 × 22.2 × 2.2 in. 967 × 564 × 57.1 mm  38.1 × 24.5 × 11.9 in. 967 × 660 × 203 mm  19.4 lbs. / 8.8 kg  26.5 lbs. / 12.0 kg  34.0 lbs. / 15.4 kg  12.8 / 12.8 / 12.8 / 19.9 mm  6.9 / 6.9 / 6.9 / 18.4 mm  100-240 Vac, 50/60 Hz  82 W / 119 W  Under 0.5 W
Solution  Smart Features  Hospitality Features  Jack Interface	Pro:Idiom (S/W Type), (Mobile, Lite)  webOS23 User Interfate	Yes  ce, Smart Home (Launcher Bar), Galler, SW Clock (World Clock / Alarm), SoftAnnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (MI Installer Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, 8 Ω), Insmote, Moving Picture Playback (SD/HD, Anti-theft System (Kensington Lo HDMI In x2 (2.0), USB  HT TV-  300 × 300 mm  1 pole (Fixed)  Dark Charcoal Gray  57.2 × 33 × 2.3 in. 1,454 × 838 × 57.7 mm  57.2 × 35.8 × 13.4 in. 1,454 × 909 × 340 mm  63 × 38.2 × 9 in. 1,600 × 970 × 228 mm  47.4 lbs. / 21.5 kg  50.5 lbs. / 22.9 kg  63.7 lbs. / 28.9 kg  12.8 / 12.8 / 12.8 / 19.9 mm  6.8 / 6.8 / 6.8 / 18.4 mm  100-240 Vac, 50/60 Hz  144 W / 180 W  Under 0.5 W  3 Year Limited	Yes  / Mode, Quick Access, Web Browser, SD P, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution PI, RS-232C), HTNG-CEC (1.4), Simplink (I  ort Block, Welcome Screen (Splash Imagistant On, VLAN ID, RJP (Remote Jack Pai /Plus HD), Auto Off / Sleep Timer, Energick, Credenza/Security Aperture (Except  In (2.0), RS-232C In (3.5 mm TRRS), Spei  John In (2.0), USB In (2.0), Antenna/Cable Link CFG (3.5 mm TRS) (b-LAN Service),  300 × 300 mm  1 pole (Swivel)  Dark Charcoal Gray  48.6 × 28.1 × 2.3 in. 1,235 × 715 × 57.5 mm 48.6 × 28.1 × 2.3 in. 1,235 × 715 × 57.5 mm 48.6 × 30.6 × 11.9 in. 1,235 × 777 × 303 mm 53.5 × 33.9 × 8.1 in. 1,360 × 860 × 207 mm 30.9 lbs. / 14.0 kg 37.9 lbs. / 17.2 kg 49.2 lbs. / 22.3 kg  12.8 / 12.8 / 12.8 / 19.9 mm 6.9 / 6.9 / 6.9 / 18.4 mm  100-240 Vac, 50/60 Hz 135 W / 163 W Under 0.5 W 3 Year Limited	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, J. IoT, EZ-Manager, USB Cloning, Wake on HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e). Insert Image, One Channel Map (LCC) (Compatibility (Teleadapt/Guestlink (IV) Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Serven In (Dual b-LAN), Optical Digital Audio OLAN (RJ45), Aux LAN (RJ45), MPI Port (RJ200 × 200 mm 1 pole (Swivel) Dark Charcoal Gray 44.1 × 25.6 × 2.2 in. 1,121 × 651 × 57.1 mm 44.1 × 28.1 × 11.9 in. 1,121 × 713 × 303 mm 51.9 × 31.9 × 7.4 in. 1,317 × 810 × 188 mm 26.7 lbs. / 12.1 kg 33.7 lbs. / 15.3 kg 41.0 lbs. / 18.6 kg 12.8 / 12.8 / 12.8 / 19.9 mm 7.3 / 7.3 / 7.8 / 18.4 mm 100-240 Vac, 50/60 Hz 112 W / 135 W Under 0.5 W 3 Year Limited	Yes  Ompatibility (MR18HA),  on RF, WOL,  Multi-code IR  I)  HDMI-CEC),  embedded  ice Only (3.5 mm TRS)  ut,  12)  200 × 200 mm  1 pole (Swivel)  Dark Charcoal Gray  38.1 × 22.2 × 2.2 in.  967 × 564 × 57.1 mm  38.1 × 24.5 × 11.9 in.  967 × 623 × 303 mm  42.3 × 26× 8.0 in.  1,075 × 660 × 203 mm  19.4 lbs. / 8.8 kg  26.5 lbs. / 12.0 kg  34.0 lbs. / 15.4 kg  12.8 / 12.8 / 12.8 / 19.9 mm  6.9 / 6.9 / 6.9 / 18.4 mm  100-240 Vac, 50/60 Hz  82 W / 119 W  Under 0.5 W  3 Year Limited
Solution  Smart Features  Hospitality Features  Jack Interface	Pro:Idiom (S/W Type), (Mobile, Lite)  webOS23 User Interfa  Mobile Co Diagnostics I  External: Mobile Re  Set Side  Set Rear  VESA Compatible  Stand Type  Front Color  Dimensions without Stand (Wx H x D) Dimensions without Stand (Wx H x D)  Shipping Dimensions (Wx H x D)  Weight without Stand  Weight with Stand  Shipping Weight  On Bezel Width (L/R/U/B)  Off Bezel Width (L/R/U/B)  Power Consumption (Typ. / Max.)  Standby Power Consumption	Yes  ce, Smart Home (Launcher Bar), Gallery SW Clock (World Clock / Alarm), SoftA nnection Overlay, HDMI-ARC (HDMI 2), (IP Remote), SI Compatible Protocol (Minstaller Menu, Lock Mode (Limited), Pc Speaker Out (R: 1.0 W, L: 1.0 W, B. Q), In gemote, Moving Picture Playback (SD/HD), Anti-theft System (Kensington Lower HDMI In x2 (2.0), USB HDMI In x2 (2	Yes  / Mode, Quick Access, Web Browser, SD p, Wi-Fi, Screen Share (Miracast), Smart Voice Recognition (Standalone/Solution Pl, RS-232C), HTNG-CEC (1.4), Simplink (I  ort Block, Welcome Screen (Splash Imagistant On, VLAN ID, RJP (Remote Jack Par) P(Plus HD), Auto Off / Sleep Timer, Energick, Credenza/Security Aperture (Except  In (2.0), RS-232C In (3.5 mm TRRS), Spei  DMI In (2.0), USB In (2.0), Antenna/Cable Link CFG (3.5 mm TRS) (b-LAN Service),  300 × 300 mm  1 pole (Swivel)  Dark Charcoal Gray  48.6 × 30.6 × 11.9 in. 1,235 × 715 × 57.5 mm 48.6 × 30.6 × 11.9 in. 1,235 × 777 × 303 mm 53.5 × 33.9 × 8.1 in. 1,360 × 860 × 207 mm 30.9 lbs. / 14.0 kg 37.9 lbs. / 17.2 kg 49.2 lbs. / 22.3 kg 12.8 / 12.8 / 19.9 mm 6.9 / 6.9 / 6.9 / 18.4 mm 100-240 Vac, 50/60 Hz 135 W / 163 W Under 0.5 W	P Server Compatibility, Magic Remote C Share, DIAL, Bluetooth Audio Playback, J. IoT, EZ-Manager, USB Cloning, Wake & HDMI-CEC) (1.4), IR Out (MPI, RS-232C), e), Insert Image, One Channel Map (LCN ck) Compatibility (Teleadapt/Guestlink (I y Saving Mode, Motion Eye Care, b-LAN 65"), Lock Down Plate (Except 65") aker Out/Line Out (3.5 mm Stereo), Server In (Dual b-LAN), Optical Digital Audio O LAN (RJ45), Aux LAN (RJ45), MPI Port (RJ 200 × 200 mm 1 pole (Swivel)  Dark Charcoal Gray 44.1 x 25.6 x 2.2 in. 1,121 x 651 x 57.1 mm 44.1 x 28.1 x 11.9 in. 1,121 x 713 x 303 mm 51.9 x 319 x 7.4 in. 1,317 x 810 x 188 mm 26.7 lbs. /12.1 kg 33.7 lbs. /15.3 kg 41.0 lbs. /18.6 kg 12.8 / 12.8 / 12.8 / 19.9 mm 7.3 / 7.3 / 7.8 / 18.4 mm 100-240 Vac, 50/60 Hz 112 W / 135 W Under 0.5 W	Yes  Ompatibility (MR18HA),  On RF, WOL, Multi-code IR  I)  IDMI-CEC), embedded  ice Only (3.5 mm TRS)  ut, 12)  200 × 200 mm  1 pole (Swivel)  Dark Charcoal Gray  38.1 × 22.2 × 2.2 in. 967 × 564 × 57.1 mm  38.1 × 24.5 × 11.9 in. 967 × 663 × 303 mm  42.3 × 26.8 kg. in. 1,075 × 660 × 203 mm  19.4 lbs. / 8.8 kg  26.5 lbs. / 12.0 kg  34.0 lbs. / 15.4 kg  12.8 / 12.8 / 12.8 / 19.9 mm  6.9 / 6.9 / 6.9 / 18.4 mm  100-240 Vac, 50/60 Hz  82 W / 119 W  Under 0.5 W

<sup>\*</sup> Specifications are subject to change without notice. Please make sure to check the product manual for details about product usage.



